




ROTULE SENZA CONO GUIDA PER GANCIO INFERIORE
LOWER LINK BALLS WITH OUT GUIDE CONE



Materiale: C16 /EN8

Art.	Cat.	D	d	L
414	1	44	22	35
93	2/1	56	22	45
415	2	56	25,4	45
94	2	56	28,2	45
197	2/1	56	22	35
198	2	56	25,4	35
199	2	56	28,2	35
95	3/2	64	28,2	45
1025	3	64	32	45
439	3	64	37	45
96	3	64	38	45


Tutte le rotule sono temprate

All balls are hard & tempered

Materiale: 20Mn Cr5

Art.	Cat.	D	d	L
Tipo spec. lunga durata - Long life				
1022	2	56	28,2	45
1023	3/2	64	28,2	45
1024	3	64	32	45
1028	3	64	37	45
1020	4/3	85	37	57,5
1021	4	85	51	57,5

ROTULA PER GANCIO SUPERIORE
UPPER LINK BALLS



Materiale: C16 /EN8

Art.	Cat.	D	d	L
432	1	38	19	44
383	2/1	50	19	51
384	2/1	50	22	51
90	2	50	25,4	51
91	3/2	60	25,4	51
92	3	60	32	51
1075	4	78	40	75
1074	4	78	45	75
1076	4	78	50	75

Tutte le rotule sono temprate

All balls are hard & tempered

Materiale: 20Mn Cr5

Art.	Cat.	D	d	L
Tipo spec. lunga durata - Long life				
1072	2	50	25,4	51
1073	3/2	60	25,4	51
1078	3	60	32	51
1070	4/3	78	32	64
1071	4	78	45,5	64